


## Mod. 10826.B D4

### COPOLYMER POLYPROPYLENE WATERPROOF CASE

Multi-weapons transport cases. Metal butterfly latches (on certain models). Available in 5 standard internal configurations. Self oiling free running wheels. Combination latch (optional).



METRIC MM-KG-C°



#### INTERNAL DIMENSIONS

|                 |         |
|-----------------|---------|
| <b>L LENGTH</b> | 1080 mm |
| <b>W WIDTH</b>  | 620 mm  |
| <b>D DEPTH</b>  | 260 mm  |
| <b>LID</b>      | 60 mm   |
| <b>BASE</b>     | 200 mm  |

#### EXTERNAL DIMENSIONS

|                 |         |
|-----------------|---------|
| <b>L LENGTH</b> | 1178 mm |
| <b>W WIDTH</b>  | 725 mm  |
| <b>D DEPTH</b>  | 287 mm  |

#### OTHER DATA

|                                |                      |
|--------------------------------|----------------------|
| <b>WEIGHT EMPTY</b>            | 17 Kg                |
| <b>WEIGHT WITH FOAM</b>        | 20.40 Kg             |
| <b>WEIGHT WITH CUSTOM FOAM</b> | 19.60 Kg             |
| <b>VOLUME</b>                  | 174 lt               |
| <b>BUOYANCY</b>                | 120.60 Kg/max        |
| <b>OPERATING TEMPERATURE</b>   | °C min -33 / max +90 |

IMPERIAL IN-LBS-F°



#### INTERNAL DIMENSIONS

|                 |            |
|-----------------|------------|
| <b>L LENGTH</b> | 42 1/2 in  |
| <b>W WIDTH</b>  | 24 7/16 in |
| <b>D DEPTH</b>  | 10 1/4 in  |
| <b>LID</b>      | 2 3/8 in   |
| <b>BASE</b>     | 7 7/8 in   |

#### EXTERNAL DIMENSIONS

|                 |            |
|-----------------|------------|
| <b>L LENGTH</b> | 46 3/8 in  |
| <b>W WIDTH</b>  | 28 1/4 in  |
| <b>D DEPTH</b>  | 11 5/16 in |

#### OTHER DATA

|                                |                         |
|--------------------------------|-------------------------|
| <b>WEIGHT EMPTY</b>            | 37.47 lbs               |
| <b>WEIGHT WITH FOAM</b>        | 44.97 lbs               |
| <b>WEIGHT WITH CUSTOM FOAM</b> | 43.21 lbs               |
| <b>VOLUME</b>                  | 45.96 gal               |
| <b>BUOYANCY</b>                | 265.87 lbs/max          |
| <b>OPERATING TEMPERATURE</b>   | °F min -27.4 / max +194 |