


## Mod. 2209.G

### COPOLYMER POLYPROPYLENE WATERPROOF CASE

Compact boxes for valuables and fragile items. High resistance body structure made in PP. Waterproof and crushproof. Resistant to dust and humidity.



METRIC MM-KG-C°



#### INTERNAL DIMENSIONS

|                 |        |
|-----------------|--------|
| <b>L LENGTH</b> | 220 mm |
| <b>W WIDTH</b>  | 160 mm |
| <b>D DEPTH</b>  | 95 mm  |
| <b>LID</b>      | 20 mm  |
| <b>BASE</b>     | 75 mm  |


#### EXTERNAL DIMENSIONS

|                 |        |
|-----------------|--------|
| <b>L LENGTH</b> | 246 mm |
| <b>W WIDTH</b>  | 215 mm |
| <b>D DEPTH</b>  | 112 mm |

#### OTHER DATA

|                                |                      |
|--------------------------------|----------------------|
| <b>WEIGHT EMPTY</b>            | 0.88 Kg              |
| <b>WEIGHT WITH FOAM</b>        | 0.99 Kg              |
| <b>WEIGHT WITH CUSTOM FOAM</b> | Kg                   |
| <b>VOLUME</b>                  | 3.30 lt              |
| <b>BUOYANCY</b>                | 2.30 Kg/max          |
| <b>OPERATING TEMPERATURE</b>   | °C min -33 / max +90 |

IMPERIAL IN-LBS-F°



#### INTERNAL DIMENSIONS

|                 |            |
|-----------------|------------|
| <b>L LENGTH</b> | 8 11/16 in |
| <b>W WIDTH</b>  | 6 5/16 in  |
| <b>D DEPTH</b>  | 3 3/4 in   |
| <b>LID</b>      | 13/16 in   |
| <b>BASE</b>     | 2 15/16 in |

#### EXTERNAL DIMENSIONS

|                 |            |
|-----------------|------------|
| <b>L LENGTH</b> | 9 11/16 in |
| <b>W WIDTH</b>  | 8 7/16 in  |
| <b>D DEPTH</b>  | 4 7/16 in  |

#### OTHER DATA

|                                |                         |
|--------------------------------|-------------------------|
| <b>WEIGHT EMPTY</b>            | 1.94 lbs                |
| <b>WEIGHT WITH FOAM</b>        | 2.18 lbs                |
| <b>WEIGHT WITH CUSTOM FOAM</b> | lbs                     |
| <b>VOLUME</b>                  | 0.79 gal                |
| <b>BUOYANCY</b>                | 5.07 lbs/max            |
| <b>OPERATING TEMPERATURE</b>   | °F min -27.4 / max +194 |