


## Mod. 2712.B E

### COPOLYMER POLYPROPYLENE WATERPROOF CASE

Shockproof cases realized in copolymer polypropylene material. Removable lid and counterbalance supports. Temperature rating from -33 °C to +90 °C.



METRIC MM-KG-C°



#### INTERNAL DIMENSIONS

|                 |        |
|-----------------|--------|
| <b>L LENGTH</b> | 276 mm |
| <b>W WIDTH</b>  | 200 mm |
| <b>D DEPTH</b>  | 120 mm |
| <b>LID</b>      | 35 mm  |
| <b>BASE</b>     | 85 mm  |


#### EXTERNAL DIMENSIONS

|                 |        |
|-----------------|--------|
| <b>L LENGTH</b> | 305 mm |
| <b>W WIDTH</b>  | 270 mm |
| <b>D DEPTH</b>  | 144 mm |

#### OTHER DATA

|                                |                        |
|--------------------------------|------------------------|
| <b>WEIGHT EMPTY</b>            | 1.62 Kg                |
| <b>WEIGHT WITH FOAM</b>        | 1.83 Kg                |
| <b>WEIGHT WITH CUSTOM FOAM</b> | Kg                     |
| <b>VOLUME</b>                  | 6.60 lt                |
| <b>BUOYANCY</b>                | 4.20 Kg/max            |
| <b>OPERATING TEMPERATURE</b>   | °C min '-33 / max '+90 |

IMPERIAL IN-LBS-F°



#### INTERNAL DIMENSIONS

|                 |           |
|-----------------|-----------|
| <b>L LENGTH</b> | 10 7/8 in |
| <b>W WIDTH</b>  | 7 7/8 in  |
| <b>D DEPTH</b>  | 4 3/4 in  |
| <b>LID</b>      | 1 3/8 in  |
| <b>BASE</b>     | 3 3/8 in  |

#### EXTERNAL DIMENSIONS

|                 |            |
|-----------------|------------|
| <b>L LENGTH</b> | 12 in      |
| <b>W WIDTH</b>  | 10 5/8 in  |
| <b>D DEPTH</b>  | 5 11/16 in |

#### OTHER DATA

|                                |                           |
|--------------------------------|---------------------------|
| <b>WEIGHT EMPTY</b>            | 3.57 lbs                  |
| <b>WEIGHT WITH FOAM</b>        | 4.03 lbs                  |
| <b>WEIGHT WITH CUSTOM FOAM</b> | lbs                       |
| <b>VOLUME</b>                  | 1.58 gal                  |
| <b>BUOYANCY</b>                | 9.25 lbs/max              |
| <b>OPERATING TEMPERATURE</b>   | °F min '-27.4 / max '+194 |