


## Mod. 5325.G E

### COPOLYMER POLYPROPYLENE WATERPROOF CASE

IP67 waterproof, dustproof cases. Side handles and soft grip rubber handle. Lid can be set to slide-off. Stainless steel reinforced padlockable points.



METRIC MM-KG-C°



#### INTERNAL DIMENSIONS

|                 |        |
|-----------------|--------|
| <b>L LENGTH</b> | 538 mm |
| <b>W WIDTH</b>  | 405 mm |
| <b>D DEPTH</b>  | 250 mm |
| <b>LID</b>      | 60 mm  |
| <b>BASE</b>     | 190 mm |


#### EXTERNAL DIMENSIONS

|                 |        |
|-----------------|--------|
| <b>L LENGTH</b> | 607 mm |
| <b>W WIDTH</b>  | 475 mm |
| <b>D DEPTH</b>  | 275 mm |

#### OTHER DATA

|                                |                      |
|--------------------------------|----------------------|
| <b>WEIGHT EMPTY</b>            | 7 Kg                 |
| <b>WEIGHT WITH FOAM</b>        | 8.25 Kg              |
| <b>WEIGHT WITH CUSTOM FOAM</b> | Kg                   |
| <b>VOLUME</b>                  | 53 lt                |
| <b>BUOYANCY</b>                | 37.20 Kg/max         |
| <b>OPERATING TEMPERATURE</b>   | °C min -33 / max +90 |

IMPERIAL IN-LBS-F°



#### INTERNAL DIMENSIONS

|                 |             |
|-----------------|-------------|
| <b>L LENGTH</b> | 21 3/16 in  |
| <b>W WIDTH</b>  | 15 15/16 in |
| <b>D DEPTH</b>  | 9 13/16 in  |
| <b>LID</b>      | 2 3/8 in    |
| <b>BASE</b>     | 7 1/2 in    |

#### EXTERNAL DIMENSIONS

|                 |             |
|-----------------|-------------|
| <b>L LENGTH</b> | 23 7/8 in   |
| <b>W WIDTH</b>  | 18 11/16 in |
| <b>D DEPTH</b>  | 10 13/16 in |

#### OTHER DATA

|                                |                         |
|--------------------------------|-------------------------|
| <b>WEIGHT EMPTY</b>            | 15.43 lbs               |
| <b>WEIGHT WITH FOAM</b>        | 18.18 lbs               |
| <b>WEIGHT WITH CUSTOM FOAM</b> | lbs                     |
| <b>VOLUME</b>                  | 14 gal                  |
| <b>BUOYANCY</b>                | 82.01 lbs/max           |
| <b>OPERATING TEMPERATURE</b>   | °F min -27.4 / max +194 |