# Mod. 2712.B


COPOLYMER POLYPROPYLENE WATERPROOF CASE

Shockproof cases realized in copolymer polypropylene material. Removable lid and counterbalance supports. Temperature rating from -33 °C to +90 °C.







METRIC MM-KG-C°




| INTERNAL DIMENSIONS | | EXTERNAL DIMENSIONS | | OTHER DATA | |
|---|---|---|---|---|---|
| L LENGTH | 276 mm | L LENGTH | 305 mm | WEIGHT EMPTY | 1.62 Kg |
| W WIDTH | 200 mm | W WIDTH | 270 mm | WEIGHT WITH FOAM | 1.83 Kg |
| D DEPTH | 120 mm | D DEPTH | 144 mm | WEIGHT WITH CUSTOM FOAM | Kg |
| LID | 35 mm | | | VOLUME | 6.60 lt |
| BASE | 85 mm | | | BUOYANCY | 4.20 Kg/max |
| | | | | OPERATING TEMPERATURE | °C min '-33 / max '+90 |

IMPERIAL IN-LBS-F°




| INTERNAL DIMENSIONS | | EXTERNAL DIMENSIONS | | OTHER DATA | |
|---|---|---|---|---|---|
| L LENGTH | 10 7/8 in | L LENGTH | 12 in | WEIGHT EMPTY | 3.57 lbs |
| W WIDTH | 7 7/8 in | W WIDTH | 10 5/8 in | WEIGHT WITH FOAM | 4.03 lbs |
| D DEPTH | 4 3/4 in | D DEPTH | 5 11/16 in | WEIGHT WITH CUSTOM FOAM | lbs |
| LID | 1 3/8 in | | | VOLUME | 1.58 gal |
| BASE | 3 3/8 in | | | BUOYANCY | 9.25 lbs/max |
| | | | | OPERATING TEMPERATURE | °F min '-27.4 / max '+194 |