


# Mod. 4419 BE

COPOLYMER POLYPROPYLENE WATERPROOF CASE



Metric mm-Kg-C°



### INTERNAL DIMENSIONS

L Length	445 mm
W Width	345 mm
D Depth	190 mm
Lid	47 mm
Base	143 mm


### EXTERNAL DIMENSIONS

L Length	474 mm
W Width	415 mm
D Depth	214 mm

### OTHER DATA

Weight empty	4 Kg
Weight with foam	4.70 Kg
Weight with custom foam	0 Kg
Volume	29.20 lt
Buoyancy	29.20 Kg/max
Operating temperature	°C min -33 / max +90

Imperial in-lbs-F°



### INTERNAL DIMENSIONS

L Length	17 1/2 in
W Width	13 9/16 in
D Depth	7 1/2 in
Lid	1 7/8 in
Base	5 5/8 in

### EXTERNAL DIMENSIONS

L Length	18 11/16 in
W Width	16 5/16 in
D Depth	8 7/16 in

### OTHER DATA

Weight empty	8.81 lbs
Weight with foam	10.36 lbs
Weight with custom foam	0 lbs
Volume	7.66 gal
Buoyancy	7.66 lbs/max
Operating temperature	°F min -27.4 / max +194

# Mod. 4419 BE

## ACCESSORIES



### HANDY BACKPACK CARRYING SYSTEM FOR CASES

Made of robust tear resistant polyester. Designed with adjustable and comfortable padded shoulder straps and belt.

Provided with an external pocket for small accessories, with Velcro strap.

Ideal wherever a free hand movement is required, like in outdoor activities, extreme sports, emergency, rescue, trekking, industrial field, etc.

Suitable for models 3317W, 4412, 4419 and 4820.

Color: black.



### PADDED BAG WITH ADJUSTABLE DIVIDERS

Highly durable padded bag with rubber coated handle and robust zipper with lockable Velcro pull zipper. Practical external front pouch for documents, removable shoulder strap and rubber feet on the bottom to grant better grip.

Internal adjustable padded dividers for flexible configuration.

Ideal to protect sensitive equipment (ie electronic, photographic, broadcasting, medical etc.).


Suitable for case 4419.

Color: black.



### PATENTED COMBINATION PADLOCK

Designed to fit snug to the Explorer case mould so as not to swing out



### PATENTED HEAVY DUTY BRASS PADLOCK WITH KEYS

Designed to fit snug to the Explorer case mould so as not to swing out



### **TSA APPROVED PADLOCK WITH COMBINATION**

The new TSA approved padlocks allow tsa® airport security agents to open the case without destroying the lock. TSA agents are trained to recognize the travel sentry certified logo and should not break the case lock.



### **FOAM SET FOR CASE 4419**

Layers of pre cubed foam for the bottom and convoluted foam for the lid



### **BLIND INSERT**

Kit includes 6 pcs.

Whenever the slots are not going to be used for in-built applications, those can be closed by blind inserts that will give the case a better and finished interior look.





### **METAL BRACKET**

Kit includes 6 pcs.

All models (except for the 1908) are internally equipped with specific slots, to apply the optional metal or plastic brackets which provide either a panel's fixing points or a fix mechanical joint inside the case, to build more complete applications. This way the case becomes a real workstation, rather than just a carrying container. As the panel mounting brackets are mechanically fixed by screws, they can be removed when necessary. The dedicated screws allow the case to remain waterproof, and help the panels to be removed easily and quickly



### **PLASTIC BRACKET**

Kit includes 6 pcs.

All models (except for the 1908) are internally equipped with specific slots, to apply the optional metal or plastic brackets which provide either a panel's fixing points or a fix mechanical joint inside the case, to build more complete applications. This way the case becomes a real workstation, rather than just a carrying container. As the panel mounting brackets are mechanically fixed by screws, they can be removed when necessary. The dedicated screws allow the case to remain waterproof, and help the panels to be removed easily and quickly



### **CONVOLUTED FOAM SET FOR CASE 4412 AND 4419**

(includes 2 pcs.)



### **LID PANEL WITH ORGANIZED POUCHES**

Practical and robust lid panel with pouches, ideal for small accessories and documents.

Suitable for cases 4412 and 4419.

Color: black.



### **PANEL RING FOR CASE 4412 AND 4419**

Includes Metric system fixing screws.

User friendly panel frames, they can be used to fix several kind of panels, from plastic to aluminum ones. Equipped with an additional gasket (which will be squeezed in between the panel and the frame) they can provide the case with a perfect instrumentation surface and a further humidity and dust resistance when the case is used in the field.

Completely removable, resistant and light, these panel rings help to transform the Explorer cases into practical workstations.



### **PANEL RING FOR CASE 4412 AND 4419**

Includes Imperial system fixing screws.

User friendly panel frames, they can be used to fix several kind of panels, from plastic to aluminum ones. Equipped with an additional gasket (which will be squeezed in between the panel and the frame) they can provide the case with a perfect instrumentation surface and a further humidity and dust resistance when the case is used in the field.

Completely removable, resistant and light, these panel rings help to transform the Explorer cases into practical workstations.



### **ADJUSTABLE SHOULDER KIT**

The kit is composed by: shoulder strap with plastic endings, 4 threaded knots, 2 metal plates. (min. extension 106 cm, max. extension 201 cm). The strap comes with the Explorer logo. Suitable for models: 1908, 1913, 2209, 2214, 4412, 4419, 5117, 9413, 11413 and 13513.



### **PROTECTIVE SLEEVE FOR PC 13"-13.3"**

Protective padded notebook sleeve. Protects the laptop from shocks and scratches.



OPTIONAL  
TOP COVERS  
AVAILABLE  
FOR LARGER  
MODELS

COVERCHI  
OPZIONALI  
PER I  
MODELLI  
PIU' GRANDI



### TOP COVER FOR DIV4412 AND DIV4419

Top covers available for larger models: they can be easily fixed on the dividers by Velcro strips. Ideal to protect and keep items in place.



### PADDED DIVIDER FOR 4419

Padded dividers with internal adjustable partitions. Ideal to protect and transport any kind of sensitive equipment. Thanks to their modularity, they can be easily combined.

## FEATURES



Additional fixing points on the lid, available on certain models



Internal slots for optional panel mounting brackets or panel mounting rings



(from model 3818 on)



By releasing the back screw, lid becomes set to slide-off when opened at 70°



The internal stop ring prevents valve from being completely extracted (Art. PURGEVALVE.B)



(art. SHOULDERKIT.U)



(Art. LABELCOVER + nr. art.)



(Art. NEOSEAL + nr. art.)



Asa de carga comprobada, reforzada con pasadores de acero a prueba de corrosión