


## Mod. 4419.G

### COPOLYMER POLYPROPYLENE WATERPROOF CASE

Waterproof cases providing a solution for any equipment requiring a high level protection. Exclusive PP based injection molded body grants superior resistance.



METRIC MM-KG-C°



#### INTERNAL DIMENSIONS

|                 |        |
|-----------------|--------|
| <b>L</b> LENGTH | 445 mm |
| <b>W</b> WIDTH  | 345 mm |
| <b>D</b> DEPTH  | 190 mm |
| <b>LID</b>      | 47 mm  |
| <b>BASE</b>     | 143 mm |


#### EXTERNAL DIMENSIONS

|                 |        |
|-----------------|--------|
| <b>L</b> LENGTH | 474 mm |
| <b>W</b> WIDTH  | 415 mm |
| <b>D</b> DEPTH  | 214 mm |

#### OTHER DATA

|                                |                        |
|--------------------------------|------------------------|
| <b>WEIGHT EMPTY</b>            | 4 Kg                   |
| <b>WEIGHT WITH FOAM</b>        | 4.70 Kg                |
| <b>WEIGHT WITH CUSTOM FOAM</b> | Kg                     |
| <b>VOLUME</b>                  | 29.20 lt               |
| <b>BUOYANCY</b>                | 29.20 Kg/max           |
| <b>OPERATING TEMPERATURE</b>   | °C min '-33 / max '+90 |

IMPERIAL IN-LBS-F°



#### INTERNAL DIMENSIONS

|                 |            |
|-----------------|------------|
| <b>L</b> LENGTH | 17 1/2 in  |
| <b>W</b> WIDTH  | 13 9/16 in |
| <b>D</b> DEPTH  | 7 1/2 in   |
| <b>LID</b>      | 1 7/8 in   |
| <b>BASE</b>     | 5 5/8 in   |

#### EXTERNAL DIMENSIONS

|                 |             |
|-----------------|-------------|
| <b>L</b> LENGTH | 18 11/16 in |
| <b>W</b> WIDTH  | 16 5/16 in  |
| <b>D</b> DEPTH  | 8 7/16 in   |

#### OTHER DATA

|                                |                           |
|--------------------------------|---------------------------|
| <b>WEIGHT EMPTY</b>            | 8.81 lbs                  |
| <b>WEIGHT WITH FOAM</b>        | 10.36 lbs                 |
| <b>WEIGHT WITH CUSTOM FOAM</b> | lbs                       |
| <b>VOLUME</b>                  | 7.66 gal                  |
| <b>BUOYANCY</b>                | 7.66 lbs/max              |
| <b>OPERATING TEMPERATURE</b>   | °F min '-27.4 / max '+194 |