


Mod. 5140.BKTE.AH**COPOLYMER POLYPROPYLENE WATERPROOF CONTAINER**

Polypropylene waterproof containers with extractable drawers. This trolley is specifically engineered for the professionals who need to carry a variety of tools and spare components. Pivoting wheels on demand.

THIS PRODUCT IS POWERED BY INTELLIRESPOND, the free App that allows for personal tool inventory and control of the content. Please visit www.intellirespond.com



METRIC MM-KG-C°

**INTERNAL DIMENSIONS**

L LENGTH	516 mm
W WIDTH	296 mm
D DEPTH	402 mm
LID	mm
BASE	mm

EXTERNAL DIMENSIONS

L LENGTH	581 mm
W WIDTH	381 mm
D DEPTH	455 mm

OTHER DATA

WEIGHT EMPTY	9.75 Kg
WEIGHT WITH FOAM	Kg
WEIGHT WITH CUSTOM FOAM	Kg
VOLUME	lt
BUOYANCY	Kg/max
OPERATING TEMPERATURE	°C min -33 / max +90

IMPERIAL IN-LBS-F°



INTERNAL DIMENSIONS

L LENGTH	20 5/16 in
W WIDTH	11 5/8 in
D DEPTH	15 13/16 in
LID	in
BASE	in

EXTERNAL DIMENSIONS

L LENGTH	22 7/8 in
W WIDTH	15 in
D DEPTH	17 15/16 in

OTHER DATA

WEIGHT EMPTY	21.49 lbs
WEIGHT WITH FOAM	lbs
WEIGHT WITH CUSTOM	lbs
FOAM	
VOLUME	gal
BUOYANCY	lbs/max
OPERATING	°F min -27.4 / max
TEMPERATURE	+194