Mod. 5326.B E

COPOLYMER POLYPROPYLENE WATERPROOF CASE


Transport cases resistant to chemicals, humidity and dust. Resistant to harshest temperatures (-33°C / +90°C). Custom foams available on demand. Self oiling free running wheels.








METRIC MM-KG-C°



INTERNAL DIMENSIONS		EXTERNAL DIMENSIONS		OTHER DATA	
L LENGTH	538 mm	L LENGTH	627 mm	WEIGHT EMPTY	10 Kg
W WIDTH	405 mm	W WIDTH	475 mm	WEIGHT WITH FOAM	11.25 Kg
D DEPTH	250 mm	D DEPTH	292 mm	WEIGHT WITH CUSTOM FOAM	Kg
LID	60 mm			VOLUME	53 lt
BASE	190 mm			BUOYANCY	37.20 Kg/max
				OPERATING TEMPERATURE	°C min -33 / max +90

IMPERIAL IN-LBS-F°



INTERNAL DIMENSIONS		EXTERNAL DIMENSIONS		OTHER DATA	
L LENGTH	21 3/16 in	L LENGTH	24 11/16 in	WEIGHT EMPTY	22.04 lbs
W WIDTH	15 15/16 in	W WIDTH	18 11/16 in	WEIGHT WITH FOAM	24.80 lbs
D DEPTH	9 13/16 in	D DEPTH	11 1/2 in	WEIGHT WITH CUSTOM FOAM	lbs
LID	2 3/8 in			VOLUME	14 gal
BASE	7 1/2 in			BUOYANCY	82.01 lbs/max
				OPERATING TEMPERATURE	°F min -27.4 / max +194