


## Mod. 5823.B E

### COPOLYMER POLYPROPYLENE WATERPROOF CASE

Watertight cases offer absolute protection in the harshest environment for all kinds of sensitive instrumentation. Practical side handles and padlockable points.



METRIC MM-KG-C°



#### INTERNAL DIMENSIONS

|                 |        |
|-----------------|--------|
| <b>L LENGTH</b> | 580 mm |
| <b>W WIDTH</b>  | 440 mm |
| <b>D DEPTH</b>  | 220 mm |
| <b>LID</b>      | 60 mm  |
| <b>BASE</b>     | 160 mm |


#### EXTERNAL DIMENSIONS

|                 |        |
|-----------------|--------|
| <b>L LENGTH</b> | 670 mm |
| <b>W WIDTH</b>  | 510 mm |
| <b>D DEPTH</b>  | 262 mm |

#### OTHER DATA

|                                |                      |
|--------------------------------|----------------------|
| <b>WEIGHT EMPTY</b>            | 9.17 Kg              |
| <b>WEIGHT WITH FOAM</b>        | 10.40 Kg             |
| <b>WEIGHT WITH CUSTOM FOAM</b> | Kg                   |
| <b>VOLUME</b>                  | 56.10 lt             |
| <b>BUOYANCY</b>                | 36.70 Kg/max         |
| <b>OPERATING TEMPERATURE</b>   | °C min -33 / max +90 |

IMPERIAL IN-LBS-F°



#### INTERNAL DIMENSIONS

|                 |             |
|-----------------|-------------|
| <b>L LENGTH</b> | 22 13/16 in |
| <b>W WIDTH</b>  | 17 5/16 in  |
| <b>D DEPTH</b>  | 8 11/16 in  |
| <b>LID</b>      | 2 3/8 in    |
| <b>BASE</b>     | 6 5/16 in   |

#### EXTERNAL DIMENSIONS

|                 |            |
|-----------------|------------|
| <b>L LENGTH</b> | 26 3/8 in  |
| <b>W WIDTH</b>  | 20 1/16 in |
| <b>D DEPTH</b>  | 10 5/16 in |

#### OTHER DATA

|                                |                         |
|--------------------------------|-------------------------|
| <b>WEIGHT EMPTY</b>            | 20.21 lbs               |
| <b>WEIGHT WITH FOAM</b>        | 22.92 lbs               |
| <b>WEIGHT WITH CUSTOM FOAM</b> | lbs                     |
| <b>VOLUME</b>                  | 14.79 gal               |
| <b>BUOYANCY</b>                | 80.90 lbs/max           |
| <b>OPERATING TEMPERATURE</b>   | °F min -27.4 / max +194 |