



www.explorercases.com

🕒 🔛 🖪



RACCK EXPL®RER



Robust —— handles offer good grip in all conditions



VIDEO PRODUCTION

WATERPROOF Rack Mount Cases



- These WATERPOOF cases are IP67 and MIL STAN certified, therefore tested to be used in rough handling conditions.

- They represent the best price/performance solution in the industry.

Offer practical fixing of standard 19" rack devices, in the specified length and up to a certain number of "U".
All models allow for an easy removal of the lid to have full access to the panels of the equipment.







The provided M6 Cage Nuts and screws grants practical mounting of any device.

Padlock-able in many points with EXPLORER CASES' patented padlocks or any commercial ones.



Silent and reliable wheels for a practical transportation



Mod. 7641



STUDIO RECORDING AUDIO & VIDEO GEAR



Mod. 5140.B.6U

6U rack-size case Units fit horizontally in the front side of the case.

EXTERNAL DIM. (L-W-D): 581x381x455 mm 22.87x15x17.91 in RACK DEPTH: 265 mm (245 mm if backword positioning) 10.43 in (9.64 in if backword positioning) LID DEPTH: 20 mm (40 mm if backword positioning) 0.78 in (1.57 in if backword positioning) EMPTY WEIGHT: kg 9,2 - 20.28 lbs

> - Practical lightweight and economical solutions to carry small rack devices up to БЦ.

> - This case can be used in horizontal mode up to 6U or in vertical mode up to 5U. - The internal hardware can easily be reconfigured for either ones of the two versions.

- Handles on both side and wheels plus trolley handle in the rear allow for a practical carrying of this case.

HORIZONTAL USE (6U)

5U rack-size case Units fit vertically from the top of the case.

RACK DEPTH: 325 mm (385 mm if forward positioning) 12.79 in (15.15 in if forward positioning) LID DEPTH: 75 (15 mm if forward positioning) 2.95 in (0.59 in if forward positioning) EMPTY WEIGHT: kg 9,2 - 20.28 lbs

ERTICAL USE (5U)



4 self-oiling free running wheels and trolley handle



LIVE STREAMING

Lids can be left in position or completely removed for an easier use on location.

15U waterproof cases with wheels and trolley handle, in two different rack depths.
These two models are provided with an internal alu racking frame that can be pulled out by mean of the practical handles, for cabling or stand-alone use.



Mod. 7630.B.15U 15U rack-size case

EXTERNAL DIM. (L-W-D): 860x560x355 mm 33.85x22.04x13.97 in RACK LENGTH: 220 mm - 8.66 in LID DEPTH: 65 mm - 2.55 in EMPTY WEIGHT: kg 16,6 - 36.59 lbs

Mod. 7641.B.15U

15U rack-size case

EXTERNAL DIM. (L-W-D): 860x560x460 mm 33.85x22.04x18.11 in RACK LENGTH: 330 mm - 12.99 in LID DEPTH: 65 mm - 2.55 in EMPTY WEIGHT: kg 18,3 - 40.34 lbs





SOFT LIVE SOUND Rack Mount Cases

RIGIDIZED BODY IN 600D POLYESTER WITH INNER HONEY COMB STRUCTURAL BODY AND SOFT PADDING ERGONOMIC HANDLE WITH RUBBER GRIP FOR EASY TRANSPORTATION

RACK



INTERNAL ALU FRAME CONSTRUCTION GRANTS RIGIDITY



4 RUBBER FEET

LARGE ZIPPERED POCKETS FOR CABLES AND ACCESSORIES

FRONT AND REAR OPENING CAN BE SECURED ON THE PADLOCKABLE ZIPPER

> RECESSED STEEL RACK RAILS





ART. BACKPACK KIT - OPTIONAL REMOVABLE SHOULDER STRAP, ALLOWS EASY CARRYING FOR ALL THREE MODELS AS BACKPACK

DATA RACKS

RACK

Mod. SOFT RACK 20

2U rack-size soft case

EXTERNAL DIM. (L-W-D): 488x536x133 mm 19.21x21.10x5.23 in RACK DEPTH: 420 mm - 16.53 in LID DEPTH: 50 mm - 1.96 in EMPTY WEIGHT: kg 2,9 - 6.39 lbs



Mod. SOFT RACK 4U 4U rack-size soft case

EXTERNAL DIM. (L-W-D): 488x536x234 mm 19.21x21.10x9.21 in RACK DEPTH: 420 mm - 16.53 in LID DEPTH: 50 mm - 1.96 in EMPTY WEIGHT: kg 3,5 - 7.71 lbs

Mod. SOFT RACK 6U 6U rack-size soft case

EXTERNAL DIM. (L-W-D): 488x536x318 mm 19.21x21.10x12.51 in RACK DEPTH: 420 mm - 16.53 in LID DEPTH: 50 mm - 1.96 in EMPTY WEIGHT: kg 4,1 - 9.03 lbs





GT LINE srl - Via del Lavoro, 9 - Loc. Crespellano 40053 Valsamoggia (Bo) - Italy Tel. +39 051 65041 - Fax +39 051 734925 www.explorercases.com - sales@explorercases.com



6

00

